

Application Serial No. 09/900,927

LISTING OF CLAIMS

Please amend Claims 21, 67, 74, 76, 84-87, 92, 98 and 102 as follows.

1 1-20 (Cancelled)

2 21. (Currently Amended) In a batting of a type having opposing faces and
3 a softness and a flexibility and configured for use in the formation of a quilt, the
4 quilt having at least one cover to be securably attached to the batting by spaced
5 apart connectors, the improvement comprising:

6 the batting consisting of cotton or polyester or cotton-polyester; and
7 having an adhesive provided with applied throughout the batting;

8 so that the at least one cover can be attached to the batting by an
9 adhesive connection at the opposing faces of the batting during formation of the
10 quilt.

1 22. (Previously Added) The batting of Claim 21 wherein the adhesive is
2 an activatable adhesive for attachment of the cover to the batting.

1 23. (Previously Added) The batting of Claim 21 wherein the adhesive is
2 applied to the batting to at least temporarily secure the cover to the batting.

24. (Canceled).

25. (Canceled).

1 26. (Previously Amended) The batting of Claim 21 wherein the adhesive
2 is activated by heat when applying the cover for attachment to the batting.

27. (Canceled).

1 28. (Previously Amended) The batting of Claim 21 wherein the adhesive
2 connection is formed by application of pressure.

Application Serial No. 09/900,927

1 29. (Previously Added) The batting of Claim 28 wh rein the application
2 of heat is provided by an iron.

30. (Canceled).

1 31. (Previously Amended) The batting of Claim 21 wherein the adhesive
2 comprises a water-soluble material.

1 32. (Previously Added) The batting of Claim 21 wherein the adhesive is
2 applied to substantially all of an interface for attachment of the cover.

33. (Canceled).

1 34. (Previously Amended) The batting of Claim 22 wherein the adhesive
2 is applied to a portion of the batting.

1 35. (Previously Amended) The batting of Claim 21 wherein the adhesive
2 is applied to at least one of the opposing faces of the batting as a pattern.

1 36. (Previously Added) The batting of Claim 21 wherein the adhesive is
2 applied by spraying to at least one of the opposing faces of the batting as a pattern.

1 37. (Previously Amended) The batting of Claim 21 wherein the adhesive
2 is removable.

38. (Canceled).

1 39. (Previously Amended) The batting of Claim 21 wherein the batting is
2 a thick material relative to a fabric cover of the quilt.

40 (Canceled).

41-66 (Withdrawn).

3 Attorney Docket No. 074313-0102

001.1412773

Received from <4143197016> at 4/23/03 9:40:13 PM [Eastern Daylight Time]

Application Serial No. 09/900,927

1 67. (Currently Amended) A batting of a type having a pair of opposing
2 faces and configured to form a soft and flexible quilt by attachment of a cover by
3 spaced apart connectors, the batting consisting of cotton or polyester or cotton-
4 polyester blend; and having an adhesive provided with applied to provide an
5 interface on at least one of the opposing faces the batting; so that a cover can be
6 at least temporarily secured to the batting with the adhesive at the interface by
7 application of heat before the cover is attached to the batting with connectors to
8 form a soft and flexible quilt.

1 68. (Previously Added) The batting of Claim 67 wherein application of
2 heat is provided by an ironing unit.

1 69. (Previously Added) The batting of Claim 67 wherein the application
2 of heat is by pressing.

1 70. (Previously Added) The batting of Claim 67 wherein the adhesive is
2 an activatable adhesive.

1 71. (Previously Added) The batting of Claim 67 wherein the adhesive
2 temporarily attaches the cover to the batting.

1 72. (Previously Added) The batting of Claim 67 wherein the adhesive is
2 provided in a thin coating to maintain the complete flexibility and softness of the
3 quilt formed by attachment of a cover to each of the opposing faces of the batting.

1 73. (Previously Added) The batting of Claim 67 wherein the adhesive
2 comprises a nonwoven material.

1 74. (Currently Amended) The batting of Claim 67 ~~wherein the adhesive is~~
2 ~~applied to the opposing faces~~ consisting of cotton or polyester or cotton-polyester
3 that is needle punched.

Application Serial No. 09/900,927

1 75. (Previously Added) The batting of Claim 67 wherein the adhesive is
2 applied to at least a portion of the opposing faces in a pattern.

1 76. (Currently Amended) The batting of Claim 67 wherein the adhesive
2 ~~provides an~~ is applied throughout the interface for attachment of the cover to the
3 batting.

1 77. (Previously Added) The batting of Claim 67 wherein the adhesive is
2 applied to a portion of the batting.

1 78. (Previously Added) The batting of Claim 67 wherein the adhesive is
2 applied to the batting by spraying at least one of the opposing faces.

1 79. (Previously Added) The batting of Claim 67 wherein the adhesive
2 comprises a water-soluble material.

1 80. (Previously Added) The batting of Claim 67 wherein the adhesive is
2 inactive until activated by application of heat and pressure.

1 81. (Previously Added) The batting of Claim 67 wherein the adhesive is
2 applied to at least one of the opposing faces of the batting as a thin layer.

1 82. (Previously Added) The batting of Claim 67 wherein the adhesive is
2 removable by washing.

1 83. (Previously Added) The batting of Claim 67 comprising a loft that is
2 thick relative to a fabric cover of the quilt.

1 84. (Currently Amended) The batting of Claim 67 wherein the adhesive
2 will remain in the quilt formed after attachment of covers to each of the opposing
3 faces of the batting by spaced-apart connectors ~~such as yarn or thread~~.

1 85. (Currently Amended) The batting of Claim 67 wherein the batting
2 consists essentially of cotton and polyester with the adhesive.

Application Serial No. 09/900,927

1 86. (Currently Amended) In a batting of a type having opposing faces and
2 a softness and a flexibility and configured for use in the formation of a quilt, the
3 quilt having at least one cover to be securably attached to the batting by spaced
4 apart connectors, the improvement comprising:

5 the batting consisting of cotton or polyester or cotton-polyester and having
6 an adhesive on each of the opposing faces;

7 so that the at least one cover can be attached to the batting by an adhesive
8 connection at the opposing faces of the batting during formation of the quilt. A
9 batting of a type having a pair of opposing faces and configured to form a soft and
10 flexible quilt by attachment of a cover to each of the opposing faces by spaced
11 apart connectors, the batting comprising:

12 a left consisting of cotton or polyester or cotton-polyester blend; and
13 an adhesive provided with the batting;

14 so that a cover can be at least temporarily secured to each of the
15 opposing faces of the batting with the adhesive before the cover is attached to the
16 batting with connectors to form a quilt.

1 87. (Currently Amended) The batting of Claim 86 wherein the adhesive is
2 provided on each of the opposing faces consisting of cotton or polyester or cotton-
3 polyester that is needle punched.

1 88. (Previously Added) The batting of Claim 86 wherein the adhesive will
2 remain in the quilt after the cover is attached to the batting by spaced apart
3 connectors.

1 89. (Previously Added) The batting of Claim 86 wherein the adhesive is
2 activatable.

1 90. (Previously Added) The batting of Claim 86 wherein the cover is at
2 least temporarily secured to the batting with the adhesive by pressing the cover to
3 the batting.

Application Serial No. 09/900,927

1 91. (Previously Added) The batting of Claim 86 wherein the cover is at
2 least temporarily secured to the batting with the adhesive by application of heat.

1 92. (Currently Amended) The batting of Claim 86 wherein the adhesive is
2 applied as a coating to the batting left.

1 93. (Previously Added) The batting of Claim 86 wherein the application
2 of heat by an iron secures the cover to the batting.

1 94. (Previously Added) The batting of Claim 86 wherein the adhesive
2 comprises a water-soluble adhesive.

1 95. (Previously Added) The batting of Claim 86 wherein the adhesive
2 provides an interface between the cover and the batting.

1 96. (Previously Added) The batting of Claim 86 wherein the adhesive is
2 provided to a portion of the batting.

1 97. (Previously Added) The batting of Claim 86 wherein the adhesive is
2 applied by spraying to at least one of the opposing faces of the batting.

1 98. (Currently Amended) The batting of Claim 86 wherein the ~~left~~ batting
2 is thick relative to a fabric cover for the quilt.

1 99. (Previously Added) The batting of Claim 86 wherein the adhesive
2 comprises a non-woven material.

1 100. (Previously Added) The batting of Claim 86 wherein the adhesive is
2 applied to the batting in a pattern.

1 101. (Previously Added) The batting of Claim 86 wherein the adhesive is
2 removable by washing.

Application Serial No. 09/900,927

- 1 102. (Currently Amended) The batting of Claim ~~86~~ 21 consisting of cotton
2 or polyester or cotton-polyester that is needle punched wherein the left comprises a
3 low left material that comprises 80 percent cotton and 20 percent polyester.

8 Attorney Docket No. 074313-0102

001.1412773

Received from <4143197016> at 4/23/03 9:40:13 PM [Eastern Daylight Time]